

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A capacitive ultrasonic transducer comprising at least one cavity defined by a first support electrode, insulating support walls forming with the support electrode wells, and a membrane electrode supported by the support walls and spaced from the support electrode, and defining the at least one cavity with the support electrode and the support walls, characterized in that, at least one isolation post or area of insulating material is formed in said at least one cavity to prevent contact of the membrane electrode to the support electrode during operation of the transducer and minimize accumulation of charge.
2. (Original) A capacitive ultrasonic transducer as in claim 1 in which the support electrode is a low resistance silicon support and the support walls are an oxide, and the membrane is silicon.
3. (Currently Amended) A capacitive ultrasonic transducer as in claims 1 or 2 in which the at least one isolation post or area is carried by the support electrode.
4. (Currently Amended) A capacitive ultrasonic transducer as in claims 1 or 2 in which the at least one isolation post or area is carried by the membrane.
5. (Currently Amended) A capacitive ultrasonic transducer as in claims 1 or 2 in which the at least one isolation post or area is ~~isolation posts or areas are~~ located at a selected location[[s]] with the size, shape, and height selected to prevent shorting between electrodes and minimize the number of trapped ions.
6. (Currently Amended) A capacitive ultrasonic transducer as in claim 5 in which the height, shape and location of the at least one isolation post or area ~~posts or areas~~ is selected so that the membrane comes in contact with the at least one isolation post or area ~~posts~~ during post contact operation of the transducer.

7. (Currently Amended) A capacitive ultrasonic transducer comprising:
at least one cavity defined by a support substrate forming a first electrode of said transducer, walls of insulating material on said support and a thin membrane supported by said walls and forming the second electrode of said transducer; and
at least one post or area of dielectric isolation material in said at least one cavity for limiting the deflection of said membrane during operation to prevent contact of the membrane with the support substrate during operation of the transducer and minimize accumulation of charge.
8. (Original) A capacitive transducer as in claim 7 in which the membrane material is selected from silicon, silicon nitride, sapphire or diamond.
9. (Currently Amended) A capacitive ultrasonic transducer as in claims 7 or 8 in which the at least one isolation post or area ~~posts or areas~~ of dielectric isolation material ~~are~~ is a dielectric isolation material.
10. (Original) A capacitive ultrasonic transducer as in claim 9 in which the walls of insulating material are a dielectric isolation material.
11. (Currently Amended) A capacitive ultrasonic transducer as in claims 7 or 8 in which the at least one isolation post or area ~~is posts or areas~~ are formed on the support substrate.
12. (Currently Amended) A capacitive ultrasonic transducer as in claims 7 or 8 in which the at least one isolation post or area ~~is posts or areas~~ are formed on the membrane.
13. (Currently Amended) A capacitive ultrasonic transducer as in claims 7 or 8 in which the location of the at least one isolation post or area ~~posts or areas~~ is chosen to optimize the frequency response of the transducer.
14. (Currently Amended) A capacitive ultrasonic transducer as in claim 13 in which the size, shape and height of the at least one isolation post or area ~~posts or areas~~ is further chosen to optimize the frequency response of the transducer.

15. (Currently Amended) A capacitive ultrasonic transducer comprising at least one cavity defined by a first support electrode, insulating support walls forming with the support electrode wells and a membrane electrode supported by the support walls and spaced from the support electrode, and defining the at least one cavity with the support electrode and the support walls, characterized in that, at least one isolation post or area of insulating material is formed in said at least one cavity to prevent contact of the membrane electrode to the support electrode during operation of the transducer and minimize accumulation of charge.

16. (Original) A capacitive ultrasonic transducer as in claim 15 with any combination of one or more posts or areas at any selected location with height, size and shape which prevents shorting between the electrodes during operation of the transducer and minimizes accumulation of charges.

17. (Currently Amended) A capacitive ultrasonic transducer comprising at least one cavity defined by a first support electrode, insulating support walls forming wells with the support electrode, and a membrane electrode supported by the support walls and spaced from the support electrode, characterized in that, at least one isolation post or area of insulating material is formed in said at least one cavity to prevent contact of the membrane electrode to the support electrode during operation of the transducer and minimize accumulation of charge.